

Series FDR

Fast DIScharge Resistor with a low-ohmic value ensures discharge of all capacities in a crash event. The unique functionality of this resistor provides safe disconnection after full discharge in the beginning of a possible new pulse.

Features


- Safe opening functionality
- Low resistance
- Fast opening time



Technical Specifications

Resistance value	0.1 Ω to 1 Ω
Resistance tolerance	$\pm 5\%$ to $\pm 10\%$
Operating voltage	1000 V
Typical pulse load capability	1000 J
Weight	~ 40 g

Dimensions in mm





Disclaimer

The given statements and information herein are recommendations for the use of our products and are based on our experience in combination with applicable technical standards.

They are for guidance only and do not represent any assurance of characteristics or warranty commitments for the products or their suitability for specific applications.

The suitability of the products for the intended use by the user depends on different boundary conditions and influencing factors and is to be assessed exclusively by the user.

DISCLAIMER:

NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, IS MADE WITH RESPECT TO THE PRODUCTS, DESIGNS, DATA, INFORMATION DESCRIBED OR ANY INTELLECTUAL PROPERTY CONTAINED THEREIN. ANY WARRANTY OR GUARANTEE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE IS ALSO EXCLUDED.

The given statements and information herein reflect the current status at the time of publication.

Typing or printing errors cannot be excluded.

This publication shall not be reprinted or reproduced in whole or in part in any form or by any means without the express written permission of Miba Resistors.