

Series RST 200

Absorbes high pulse energy within a very short period. Has high thermal capacity. Used in dumping, circuit breaking etc.

Features

- Aluminum housing for better heat dissipation
- Different connection possible (FAST-ON, wires)






Technical Specifications

Resistance value	10 Ω to 300 Ω
Resistance tolerance	$\pm 5\%$ to $\pm 10\%$
Temperature coefficient	± 500 ppm/ $^{\circ}\text{C}$ (referenced to 25 $^{\circ}\text{C}$, ΔR taken at ~ 105 $^{\circ}\text{C}$)
Power rating	200 W at 70 $^{\circ}\text{C}$ Ta (120 s continuous operation)
Operating voltage	≤ 1000 V DC (pre-charge voltage)
Insulation resistance	1000 V DC, min. 500 M Ω
Short time overload	3000 W, 70 $^{\circ}\text{C}$ 3 s
Insulation layer withstand voltage	3.5 kV rms, 50 Hz, 1 min.
Operating temperature	- 55 $^{\circ}\text{C}$ to + 225 $^{\circ}\text{C}$
Mounting	M5 screw
Weight	~ 285 g


Typical Pulse Load (initial resistor temperatur ≤ 85 $^{\circ}\text{C}$)

2300 J for $\tau = 0.1$ s
3150 J for $\tau = 0.2$ s
4000 J for $\tau = 0.5$ s

Dimensions in mm



Derating Curve





Disclaimer

The given statements and information herein are recommendations for the use of our products and are based on our experience in combination with applicable technical standards.

They are for guidance only and do not represent any assurance of characteristics or warranty commitments for the products or their suitability for specific applications.

The suitability of the products for the intended use by the user depends on different boundary conditions and influencing factors and is to be assessed exclusively by the user.

DISCLAIMER:

NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, IS MADE WITH RESPECT TO THE PRODUCTS, DESIGNS, DATA, INFORMATION DESCRIBED OR ANY INTELLECTUAL PROPERTY CONTAINED THEREIN. ANY WARRANTY OR GUARANTEE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE IS ALSO EXCLUDED.

The given statements and information herein reflect the current status at the time of publication.

Typing or printing errors cannot be excluded.

This publication shall not be reprinted or reproduced in whole or in part in any form or by any means without the express written permission of Miba Resistors.